Linux CVS/RCS HOWTO document for Linux (Source Code Control System)

Al Dev (Alavoor Vasudevan) *alavoor@yahoo.com* v3.0, 23 October 1999

This document is a "practical guide" to very quickly setup CVS/RCS source code control system. This document also has custom shell scripts which are wrappers on top of CVS. These scripts provide a easy user interface for CVS. The information in this document applies to Linux and as well as to all other flavors of Unix liks Solaris, HPUX, AIX, SCO, Sinix, BSD, SCO, etc..

Contents

1 Introduction **2**

2 Which one is for me? CVS or RCS **2**

3 Setting up CVS **3**

3.1 Environment variables . . . 3

3.2 Migrate RCS to CVS . . . 4

4 Shell Scripts **5**

4.1 sget . . . 6

4.2 sedit . . . 8

4.3 scommit . . . 11

4.4 supdate . . . 14

4.5 sunlock . . . 15

4.6 slist . . . 17

4.7 sinfo . . . 19

4.8 slog . . . 20

4.9 sdif . . . 21

4.10 sadd . . . 22

4.11 sdelete . . . 23

4.12 sfreeze . . . 24

4.13 saddtree . . . 25

5 CVS Documentation **26**

6 Emacs Editor **27**

7 Other Formats of this Document **27**

1 Introduction

Source code control system is a MUST to manage the changes occuring to software project during development. Developer needs a complete history of changes to backtrack to previous versions in case of any problems. Since source code is the most vital component of any software project and software development takes a huge amount of time and money, it is very important to spend some time in ***safe-guarding*** the source code by using the source code control systems like CVS and RCS.

CVS (Concurrent Version Control System) is a powerful tool which allows concurrent development of software by multiple users. It uses RCS underneath and has application layer interface as a wrapper on top RCS.

CVS can record the history of your files (usually, but not always, source code). CVS only stores the differences between versions, instead of every version of every file you've ever created. CVS also keeps a log of who, when and why changes occurred, among other aspects.

CVS is very helpful for managing releases and controlling the concurrent editing of source files among multiple authors. Instead of providing version control for a collection of files in a single directory, CVS provides version control for a hierarchical collection of directories consisting of revision controlled files.

These directories and files can then be combined together to form a software release.

CVS can be used for storing "C", "C++", Java, Perl, HTML and other files.

2 Which one is for me? CVS or RCS

CVS actually uses RCS underneath. CVS is a lot more powerful tool and can control a complete source code tree. It is ***very strongly*** recommended that you use CVS, because you can greatly customize CVS with scripting languages like PERL, korn and bash shells. See the sample korn shell scripts at 4 ().

Advantages of CVS

- CVS is de-centralised, user checks out files/directories from the repostitory and has his own seperate stable source directory tree.
- CVS can "STAMP" releases of entire project source tree.
- CVS can enable concurrent editing of files.
- CVS can be greatly customized to enable strong locking of files or enable concurrent editing of files using shell scripts or PERL.

Dis-Advantages of CVS

- Needs little more administration than RCS
- Very highly sophisticated and complex system. It is the "State of the Art" technology.
- Has large number of commands and command options. Hence steeper learning curve for beginners. The shell scripts at 4 () can ease usage.

Advantages of RCS

- RCS is very simple to setup, less administration work.
- RCS is used in a centralized area where everyone works.
- RCS is useful for simple systems.

- Very strong locking of files - concurrency eliminated.

Downside of RCS

- Concurrent development by multiple developers is not possible due to file locking and a single working directory. Because of single working directory, code changes of files by multiple developers can cause failure of 'make' command.
- Cannot stamp releases of entire software project.

This document also has shell scripts which provide simple commands to check-out, check-in, commit files. See shell scripts at 4 ()

For RCS see the RCS mini-howto on the linux cdrom -

```
cd /mnt/cdrom/Redhat/RPMS
ls -l howto-6.0-*.noarch.rpm
rpm -qpl howto-6* | grep -i rcs
```

or visit <http://sunsite.unc.edu/LDP/HOWTO/mini/RCS-HOWTO.html>

3 Setting up CVS

First you need to install the CVS package, on Redhat linux use

```
cd /mnt/cdrom/Redhat/RPMS
rpm -i rcs*.rpm
rpm -i cvs*.rpm
To see the list of files installed do -
rpm -qpl cvs*.rpm | less
```

and browse output using j,k, CTRL+f, CTRL+D, CTRL+B, CTRL+U or using arrow keys, page up/down keys. See 'man less'.

On other flavors of unix, you may need to download the RCS and CVS tar balls and follow README, INSTALL files to setup CVS. Visit <http://www.cyclic.com> and <http://www.loria.fr/~molli/cvs-index.html>

3.1 Environment variables

The following environment variables need to be setup in /etc/profile - default values required for all users. If not set in /etc/profile, than you should add these to your local profile file /.bash_profile.

```
export EDITOR=/bin/vi
export CVSROOT=/home/cvsroot
export CVSREAD=yes
```

Create a directory to store the source code repository and give read, write access to unix group/user.

```
export CVSROOT=/home/cvsroot
mkdir $CVSROOT
chmod o-rwx $CVSROOT
chmod ug+rwx $CVSROOT
```

To initialize the CVS and to put in source code files do -

```
cvs init

# Change directory is a must
cd $HOME/my_source_code_dir

# Must give vendor tag and revision tag
cvs import my_source_code_dir V1_0 R1_0
```

3.2 Migrate RCS to CVS

To migrate the existing RCS files to CVS, use the following script. Make sure that you installed korn shell package pdksh*.rpm from Linux contrib cdrom. After running the script move the resultant directory-tree to $CVSROOT/some_project_name

NOTE : ***Korn shell /bin/ksh is got by installing pdksh*.rpm from Linux contrib cdrom***

```
#!/bin/ksh

################################################################
# Program to Migrate the existing source code in RCS to CVS
#
# Needs the korn shell RPM package  pdksh*.rpm from Linux
# contrib cdrom
################################################################

# Enter your current RCS file location here.
RCS_DIRECTORY=/usr/home/my_rcs_tree

# Temporary directory to hold the files
TMP_RCS_DIR=$HOME/tmp_rcs_directory

mkdir $TMP_RCS_DIR

# Copy the tree having RCS directory into temporary directory
cd $RCS_DIRECTORY
tar cvf -  ‘ find . -name RCS -print ‘ | ( cd $TMP_RCS_DIR; tar -xvf - )

cd $TMP_RCS_DIR

for ii in ‘find . -type f -print‘ ;
do
        # $ii will have like /home/foo/RCS/sample.c,v
        echo $ii
```

```
        # Get the dir name like /home/foo/RCS from ii
        kk=`dirname $ii`
        # echo $kk

        # Drop off RCS from kk - like /home/foo
        jj=`dirname $kk`
        #       echo $jj

        # Move file from RCS to upper leve like
        # mv /home/foo/RCS/sample.c,v  /home/foo
        mv $ii $jj
done

# Remove the empty directory RCS like -
# rmdir /home/foo/RCS
cd $TMP_RCS_DIR
find  . -type d -name RCS -exec rmdir {} \;

# The resultant directory is $TMP_RCS_DIR (which is $HOME/tmp_rcs_directory)
# Move the directory tmp_rcs_directory to $CVSROOT/some_project_name
# Now the RCS is migrated to CVS as 'some_project_name' .
```

The resultant directory is $TMP_RCS_DIR (which is $HOME/tmp_rcs_directory) Move the directory tmp_rcs_directory to $CVSROOT/some_project_name Now the RCS is migrated to CVS as 'some_project_name'. You can start using the CVS commands on module 'some_project_name'.

4 Shell Scripts

The following are wrappers around the basic CVS commands. The scripts are written for Korn shell since korn shell is always available on all flavors of unixes, but you can translate to bash or PERL if needed. You can customize these scrips to your taste. They are basically CVS commands but features are added to make it site specific. For example, sedit script provides locking so that users will know some-one is editing the file. Ofcourse users can directly use the CVS commands to by-pass these scripts. These scripts demonstrate as to how CVS can be customized to a great extent.

1. **sget** [-r revision_number] <file/directory name> To get a file or entire directory from CVS in READ ONLY mode. Click 4.1 ()
2. **sedit** [-r revision_number] <filename> To edit a file in order to make changes to code. This will lock the file so that nobody else can checkout. Ofcourse you can change the script to your requirement - make no locking, warning message or very strong locking. Click 4.2 ()
3. **scommit** [-r revision_number] <filename> To commit the changes you made to filename or entire directory. Upload your changes to CVS Click 4.3 ()
4. **supdate** <filename/directory> To update a filename or to update a entire directory by getting the latest files from CVS Click 4.4 ()
5. **sunlock** [-r revision_number] <filename> To unlock the file got by sedit. Will release the lock. Click 4.5 ()

6. **slist** To see the list of files currently being edited by you. Does 'ls -l | grep | ...' command. Click 4.6 ()
7. **sinfo** <filename/directory> To get the information of changes/revisions to a file Click 4.7 ()
8. **slog** <filename> To get the history of changes/revisions to a file from CVS Click 4.8 ()
9. **sdif** <filename> **sdif** -r rev1 -r rev2 <filename> To get the diff of your file with CVS. Click 4.9 ()
   NOTE: sdif has only one 'f' because there is already another unix command called 'sdiff'
10. **sadd** <filename> To add a new file to CVS repository Click 4.10 ()
11. **sdelete** <filename> To delete a file from CVS repository Click 4.11 ()
12. **sfreeze** <revision name> <directory name> To freeze the code, that is make release of entire source tree. Click 4.12 ()
13. **saddtree** <revision name> <directory name> To add a directory tree to CVS. Click 4.13 () For example :

```
cd $HOME;
sfreeze REVISION_1_0  srctree
```

This will freeze code with tag REVISION_1_0 so that you can later checkout the entire tree by using with revision name

****

4.1 sget

NOTE : *Korn shell /bin/ksh is got by installing pdksh*.rpm from Linux contrib cdrom*

Save this file as text file and chmod a+rx on it.

```
#!/bin/ksh

# CVS program sget
# Program to check out the file from CVS read-only

cmdname=`basename $0`

Usage()
{
        print "\nUsage: $cmdname [-r revision_number/symbolic_tag_name] <file/directory name> "
        print "The options -r are optional "
        print "For example - "
        print " $cmdname -r 1.1 foo.cpp"
        print " $cmdname foo.cpp "
        print " $cmdname some_directory "
        print "Extract by symbolic revision tag like - "
        print " $cmdname -r REVISION_1 some_directory "
        print " "
        exit
}

# Command getopt will not supported in next major release.
```

```
# Use getopts instead.
while getopts r: ii
do
        case $ii in
        r) FLAG1=$ii; OARG1="$OPTARG";;
        ?) Usage; exit 2;;
        esac
done
shift ` expr $OPTIND - 1 `

#echo FLAG1 = $FLAG1 , OARG1 = $OARG1

if [ $# -lt 1 ]; then
        Usage
fi

bkextn=sget_bak

hme=` echo $HOME | cut -f1 -d' '  `
if [ "$hme" = "" ]; then
        print "\nError: \$HOME is not set!!\n"
        exit
fi

# Check if file already exists....
if [ -f $1 ]; then
        user_perms=" "
        group_perms=" "
        other_perms=" "
        user_perms=`ls -l $1 | awk '{print $1 }' | cut -b3-3 `
        group_perms=`ls -l $1 | awk '{print $1 }' | cut -b6-6 `
        other_perms=`ls -l $1 | awk '{print $1 }' | cut -b9-9 `
        if [ "$user_perms" = "w" -o "$group_perms" = "w"  \
                -o "$other_perms" = "w" ]; then
                print "\nError: The file is writable. Aborting $cmdname ......"
                print "       You should either backup, scommit or delete the file and"
                print "       try $cmdname again\n"
                exit
        fi
fi

cur_dir=`pwd`
#echo $cur_dir

len=${#hme}
len=$(($len + 2))
#echo $len

subdir=` echo $cur_dir | cut -b $len-2000 `
#echo $subdir

if [ "$subdir" = "" ]; then
        fdname=$1
else
        fdname=$subdir"/"$1
```

```
fi

# Move the file
touch $1 2>/dev/null
\mv -f $1 $1.$bkextn

# Create subshell
(
cd $hme
#echo $fdname

# Use -A option to clear all sticky flags
if [ "$FLAG1" = "" ]; then
        cvs -r checkout -A $fdname
else
        cvs -r checkout -A -$FLAG1 $OARG1 $fdname
fi
)
#pwd

if [ -f $1 ]; then
        print "\nREAD-ONLY copy of the file $fdname obtained."
        print "Done $cmdname"
        #print "\nTip (Usage): $cmdname <file/directory name> \n"
fi
```

4.2 sedit

NOTE : ***Korn shell /bin/ksh is got by installing pdksh*.rpm from Linux contrib cdrom***

Save this file as text file and chmod a+rx on it.

```
#!/bin/ksh
# CVS program sedit
# Program to check out the file from CVS read/write mode with locking

cmdname=`basename $0`

Usage()
{
#       print "\nUsage: $cmdname [-r revision_number] [-F] <filename>"
#       print "The options -r, -F are optional "
#       print "The option -F is FORCE edit even if file is "
#       print "locked by another developer"

        print "\nUsage: $cmdname [-r revision_number] <filename>"
        print "The options -r are optional "

        print "For example - "
        print " $cmdname -r 1.1 foo.cpp"
        print " $cmdname foo.cpp "
#       print " $cmdname -F foo.cpp "
        print " "
}
```

```
# Command getopt will not supported in next major release.
# Use getopts instead.
#while getopts r:F ii
while getopts r: ii
do
        case $ii in
        r) FLAG1=$ii; OARG1="$OPTARG";;
#       F) FLAG2=$ii; OARG2="$OPTARG";;
        ?) Usage; exit 2;;
        esac
done
shift ` expr $OPTIND - 1 `

#echo FLAG1 = $FLAG1 , OARG1 = $OARG1

if [ $# -lt 1 ]; then
        Usage
        exit
fi

hme=` echo $HOME | cut -f1 -d' '  `
if [ "$hme" = "" ]; then
        print "\nError: \$HOME is not set!!\n"
        exit
fi

bkextn=sedit_bak

cur_dir=`pwd`
#echo $cur_dir

len=${#hme}
len=$(($len + 2))
#echo $len

subdir=` echo $cur_dir | cut -b $len-2000 `
#echo $subdir

if [ "$subdir" = "" ]; then
        fdname=$1
else
        fdname=$subdir"/"$1
fi

# If file is already checked out by another developer....
cvs_root=` echo $CVSROOT | cut -f1 -d' '  `
if [ "$cvs_root" = "" ]; then
        print "\nError: \$CVSROOT is not set!!\n"
        exit
fi
cldir=$CVSROOT/$subdir/Locks
mkdir $cldir 2>/dev/null
rcsfile=$CVSROOT/$subdir/$1,v
#echo $rcsfile
```

```
if [ ! -e $rcsfile ]; then
        print "\nError: File $1 does not exist in CVS repository!!\n"
        exit
fi

# Get the tip revision number of the file....
# Use tmpfile as the arg cannot be set inside the sub-shell
tmpfile=$hme/sedit-lock.tmp
\rm -f $tmpfile 2>/dev/null
if [ "$FLAG1" = "" ]; then
        (
        cd $hme
        cvs log $fdname | head -6 | grep head: | awk '{print $2}' > $tmpfile
        )
        OARG1=`cat $tmpfile`
        \rm -f $tmpfile 2>/dev/null
fi

lockfile=$cldir/$1-$OARG1
#if [ -e $lockfile -a "$FLAG2" = "" ]; then
if [ -e $lockfile ]; then
        print "\nError: File $1 Revision $OARG1 already locked by another developer !!"
        aa=` ls -l $lockfile | awk '{print "Locking developers unix login name is = " $3}' `
        print $aa
        print "That developer should do scommit OR sunlock to release the lock"
        print " "
#       print "You can also use -F option to force edit the file even if"
#       print "the file is locked by another developer. But you must talk to"
#       print "other developer to work concurrently on this file."
#       print "For example - this option is useful if you work on a seperate"
#       print "C++ function in the file which does not interfere with other"
#       print "developer."
#       print " "
        exit
fi

# Get read-only copy now....
if [ ! -e $1 ]; then
        (
        cd $hme
        cvs -r checkout $fdname 1>/dev/null
        )
fi

# Check if file already exists....
if [ -f $1 ]; then
        user_perms=" "
        group_perms=" "
        other_perms=" "
        user_perms=`ls -l $1 | awk '{print $1 }' | cut -b3-3 `
        group_perms=`ls -l $1 | awk '{print $1 }' | cut -b6-6 `
        other_perms=`ls -l $1 | awk '{print $1 }' | cut -b9-9 `
        if [ "$user_perms" = "w" -o "$group_perms" = "w"  \
                -o "$other_perms" = "w" ]; then
                print "\nError: The file is writable. Aborting $cmdname ......"
```

```
                print "       You must backup, scommit or delete file and"
                print "       try $cmdname again\n"
                exit
        fi
        #print "\nNote: The file $1 is read-only."
        #print "Hence I am moving it to $1.$bkextn ....\n"
        \mv -f $1 $1.$bkextn
        chmod 444 $1.$bkextn
elif [ -d $1 ]; then
        print "\nError: $1 is a directory and NOT a file. Aborting $cmdname ....\n"
        exit
fi

# Create subshell
print "\nNow getting the file $1 from CVS repository ...\n"
(
cd $hme
#echo $fdname
# Use -A option to clear the sticky tag and to get
# the HEAD revision version
if [ "$FLAG1" = "" ]; then
        cvs -w checkout -A $fdname
else
        cvs -w checkout -A -$FLAG1 $OARG1 $fdname
fi
)

if [ -e $1 ]; then
        touch $lockfile
fi

#pwd

print "\nDone $cmdname"
#print "\nTip (Usage): $cmdname <filename> \n"
```

4.3 scommit

NOTE : ***Korn shell /bin/ksh is got by installing pdksh*.rpm from Linux contrib cdrom***

Save this file as text file and chmod a+rx on it.

```
#!/bin/ksh
# CVS program scommit
# Program to commit the changes and check in the file into CVS

cmdname=`basename $0`

Usage()
{
        print "\nUsage: $cmdname [-r revision_number] <filename>"
        print "The options -r are optional "
        print "For example - "
        print " $cmdname -r 1.1 foo.cpp"
        print " $cmdname foo.cpp "
```

```
        print " "
}

# Command getopt will not supported in next major release.
# Use getopts instead.
while getopts r: ii
do
        case $ii in
        r) FLAG1=$ii; OARG1="$OPTARG";;
        ?) Usage; exit 2;;
        esac
done
shift ‘ expr $OPTIND - 1 ‘

#echo FLAG1 = $FLAG1 , OARG1 = $OARG1

if [ $# -lt 1 ]; then
        Usage
        exit 2
fi

if [ -d $1 ]; then
        Usage
        exit 2
fi

hme=‘ echo $HOME | cut -f1 -d’ ’  ‘
if [ "$hme" = "" ]; then
        print "\nError: \$HOME is not set!!\n"
        exit
fi

# Find sub-directory
cur_dir=‘pwd‘
#echo $cur_dir
len=${#hme}
len=$(($len + 2))
#echo $len
subdir=‘ echo $cur_dir | cut -b $len-2000 ‘
#echo $subdir
if [ "$subdir" = "" ]; then
        fdname=$1
else
        fdname=$subdir"/"$1
fi

# If file is already checked out by another user....
cvs_root=‘ echo $CVSROOT | cut -f1 -d’ ’  ‘
if [ "$cvs_root" = "" ]; then
        print "\nError: \$CVSROOT is not set!!\n"
        exit
fi
cldir=$CVSROOT/$subdir/Locks
mkdir $cldir 2>/dev/null
```

```
# Get the working revision number of the file....
# Use tmpfile as the arg cannot be set inside the sub-shell
tmpfile=$hme/sedit-lock.tmp
\rm -f $tmpfile 2>/dev/null
if [ "$FLAG1" = "" ]; then
        (
        cd $hme
        cvs status $fdname 2>/dev/null | grep "Working revision:" | awk '{print $3}' >$tmpfile
        )
        OARG1=`cat $tmpfile`
        \rm -f $tmpfile 2>/dev/null
fi

if [ "$OARG1" = "" ]; then
        print "The file $fdname is NEW, it is not in the CVS repository"
else
        lockfile=$cldir/$1-$OARG1
        if [ -e $lockfile ]; then
                # Check if this revision is owned by you...
                aa=` ls -l $lockfile | awk '{print $3}' `
                userid=`id | cut -d'(' -f2 | cut -d')' -f1 `
                if [ "$aa" != "$userid" ]; then
                        print " "
                        print "The file $fdname is NOT locked by you!!"
                        print "It is locked by unix user name $aa and your login name is $userid"
#                       print "If you are working concurrently with other developer"
#                       print "and you used -F option with sedit."
                        print "You need to wait untill other developer does scommit"
                        print "or sunlock"
                        print "Aborting the $cmdname ...."
                        print " "
                        exit 2
                fi
        else
                if [ -f $CVSROOT/$subdir/$1,v ]; then
                        print "You did not lock the file $fdname with sedit!!"
                        print "Aborting the $cmdname ...."
                        exit 2
                else
                        print "\nThe file $fdname does not exist in CVS repository yet!!"
                        print "You should have done sadd on $fdname ...."
                fi
        fi
fi

if [ -d $1 ]; then
        Usage
        exit 2
        # Do not allow directory commits for now ...
        #cvs commit
else
        cvs commit $1
        exit_status=$?
fi
```

```
if [ $exit_status -eq 0 ]; then
        print "\nDone $cmdname. $cmdname successful"
        #print "\nTip (Usage): $cmdname <filename/directory name>\n"
fi
```

4.4 supdate

NOTE : ***Korn shell /bin/ksh is got by installing pdksh*.rpm from Linux contrib cdrom***

Save this file as text file and chmod a+rx on it.

```
#!/bin/ksh

# CVS program supdate
# Program to update the file from CVS read/write mode

cmdname=`basename $0`

if [ $# -lt 1 ]; then
        print "\nUsage: $cmdname <filename>"
        exit
fi

# Check if file already exists....
if [ $# -gt 0 -a  -f $1 ]; then
        user_perms=" "
        group_perms=" "
        other_perms=" "
        user_perms=`ls -l $1 | awk '{print $1 }' | cut -b3-3 `
        group_perms=`ls -l $1 | awk '{print $1 }' | cut -b6-6 `
        other_perms=`ls -l $1 | awk '{print $1 }' | cut -b9-9 `
        if [ "$user_perms" = "w" -o "$group_perms" = "w"  \
                -o "$other_perms" = "w" ]; then
                while :
                do
                        print "\n$cmdname will backup your working file "
                        print "$1 to $1.supdate_bak before doing any merges."
                        print "Are you sure you want the merge the changes from"
                        print -n "CVS repository to your working file ? <y/n> [n]: "
                        read ans
                        if [ "$ans" = "y" -o "$ans" = "Y" ]; then
                                if [ -f $1.supdate_bak ]; then
                                        print "\nWarning : File $1.supdate_bak already exists!!"
                                        print "Please examine the file $1.supdate_bak and delete it"
                                        print "and than re-try this $cmdname "
                                        print "Aborting $cmdname ...."
                                        exit
                                else
                                        cp $1 $1.supdate_bak
                                        break
                                fi
                        elif [ "$ans" = "n" -o "$ans" = "N" -o "$ans" = "" -o "$ans" = " " ]; then
                                exit
                        fi
                done
```

```
        fi
fi

if [ -d $1 ]; then
        print "\nDirectory update is disabled as cvs update"
        print "merges the changes from repository to your working directory"
        print "So give the filename to update - as shown below: "
        print " Usage: $cmdname <filename>"
        exit
#       cvs update
else
        cvs update $1
fi

print "\nDone $cmdname. $cmdname successful"
#print "\nTip (Usage): $cmdname <filename/directory name>\n"
```

4.5 sunlock

NOTE : ***Korn shell /bin/ksh is got by installing pdksh*.rpm from Linux contrib cdrom***

Save this file as text file and chmod a+rx on it.

```
#!/bin/ksh
# CVS program sunlock
# Program to unlock the file to release the lock done by sedit

cmdname=`basename $0`

Usage()
{
        print "\nUsage: $cmdname [-r revision_number] <filename>"
        print " The options -r is optional "
        print "For example - "
        print " $cmdname -r 1.1 foo.cpp"
        print " $cmdname foo.cpp "
        print " "
}

# Command getopt will not supported in next major release.
# Use getopts instead.
while getopts r: ii
do
        case $ii in
        r) FLAG1=$ii; OARG1="$OPTARG";;
        ?) Usage; exit 2;;
        esac
done
shift ` expr $OPTIND - 1 `

if [ $# -lt 1 ]; then
        Usage
        exit
fi
```

```
hme=‘ echo $HOME | cut -f1 -d’ ’  ‘
if [ "$hme" = "" ]; then
        print "\nError: \$HOME is not set!!\n"
        exit
fi

cur_dir=‘pwd‘
#echo $cur_dir

len=${#hme}
len=$(($len + 2))
#echo $len

subdir=‘ echo $cur_dir | cut -b $len-2000 ‘
#echo $subdir

if [ "$subdir" = "" ]; then
        fdname=$1
else
        fdname=$subdir"/"$1
fi

# If file is already checked out by another user....
cvs_root=‘ echo $CVSROOT | cut -f1 -d’ ’  ‘
if [ "$cvs_root" = "" ]; then
        print "\nError: \$CVSROOT is not set!!\n"
        exit
fi
cldir=$CVSROOT/$subdir/Locks
rcsfile=$CVSROOT/$subdir/$1,v
#echo $rcsfile

if [ ! -e $rcsfile ]; then
        print "\nError: File $1 does not exist in CVS repository!!\n"
        exit
fi

# Get the tip revision number of the file....
# Use tmpfile as the arg cannot be set inside the sub-shell
tmpfile=$hme/sedit-lock.tmp
\rm -f $tmpfile 2>/dev/null
if [ "$FLAG1" = "" ]; then
        (
        cd $hme
        cvs log $fdname | head -6 | grep head: | awk ’{print $2}’ > $tmpfile
        )
        OARG1=‘cat $tmpfile‘
        \rm -f $tmpfile 2>/dev/null
fi

lockfile=$cldir/$1-$OARG1
#echo lockfile is : $lockfile
if [ ! -e $lockfile ]; then
        print "\nFile $1 revision $OARG1 is NOT locked by anyone"
        print " "
```

```
        exit
fi

ans=""
while :
do
        print "\n\n************************************************"
        print "WARNING: $cmdname will release lock and enable other"
        print "         developers to edit the file. It is advisable"
        print "         to save your changes with scommit command"
        print "************************************************"
        print -n "\nAre you sure you want to unlock the file <y/n>? [n]: "
        read ans
        if [ "$ans" = "" -o "$ans" = " " -o "$ans" = "n" -o "$ans" = "N" ]; then
                print "\nAborting $cmdname ...."
                exit
        fi
        if [ "$ans" = "y" -o "$ans" = "Y" ]; then
                print "\n\n\n\n\n "
                print "CAUTION: You may lose all the changes made to file!!"
                print -n "Do you really want to unlock the file <y/n>? [n]: "
                read ans
                if [ "$ans" = "y" -o "$ans" = "Y" ]; then
                        break
                else
                        exit
                fi
        else
                print "\n\nWrong entry. Try again..."
                sleep 1
        fi
done

if [ -e $lockfile ]; then
        \rm -f $lockfile
        print "\nDone $cmdname"
else
        print "\nFile $1 is NOT locked by anyone"
        print " "
fi
```

4.6 slist

NOTE : ***Korn shell /bin/ksh is got by installing pdksh*.rpm from Linux contrib cdrom***

Save this file as text file and chmod a+rx on it.

```
#!/bin/ksh

# CVS program slist
# Program to list all edited source files from CVS

#cmdname=`basename $0`

if [ "$1" = "" ]; then
```

```
        dir=.
else
        dir=$1
fi

FOUT=slist_temporary_file.out

\rm -f $FOUT

find $dir  -type f -exec ls -ltr {} \; \
| grep -v "/CVS/" \
| grep ^\-rw \
| grep -v \\.o \
| grep -v \\.log \
| grep -v \\.out \
| grep -v \\.pid \
| awk '{ if ($NF != "tags") print $0 }' \
| awk '{ if ($NF != "a.out") print $0 }' \
| awk '{ if ($NF != "core") print $0 }' \
| awk '{ print $NF }' > $FOUT

aa=`cat $FOUT`
\rm -f $FOUT

for ii in $aa ; do
        ftype=" "
        ftype=`file $ii | awk '{print $2 }' `

        # find . -type f -exec file {} \;
        # 1)ELF 2)commands 3)[nt]roff, 4)c 5)English  6)executable
        # 7)ascii 8)current 9)empty
        # Binaries are ELF, lib.a are current
        #
        if [ "$ftype" = "ascii" -o "$ftype" = "commands" \
                -o "$ftype" = "[nt]roff," -o "$ftype" = "c" \
                -o "$ftype" = "English" -o "$ftype" = "executable" ]; then
                pcfile=` echo $ii | cut -d'.' -f1`
                pcfile=${pcfile}".pc"
                if [ ! -f $pcfile ]; then
                        ls -l $ii
                else
                        if [ "$ii" = "$pcfile" ]; then
                                ls -l $ii
                        fi
                fi
        fi
done;

#| grep -v ^\-rwx \

#ls -l | grep ^\-rw | grep -v \\.o
#ls -l | grep ^\-rw | grep -v \\.o | awk '{ if ($NF != "tags") print $0 }'
#ls -l | grep ^\-rw | grep -v ^\-rwx | grep -v \\.o |  awk '{ if ($NF != "tags") print $0 }' | awk '{ if ($NF

#print "\nDone $cmdname. $cmdname successful"
```

```
#print "\nTip (Usage): $cmdname <filename>\n"
```

4.7 sinfo

NOTE : ***Korn shell /bin/ksh is got by installing pdksh*.rpm from Linux contrib cdrom***

Save this file as text file and chmod a+rx on it.

```
#!/bin/ksh

# CVS program sinfo
# Program to get the status of files in working directory

cmdname=`basename $0`

if [ $# -lt 1 ]; then
        print "\nUsage: $cmdname [file/directory name] "
        print "For example - "
        print " $cmdname foo.cpp"
        print " $cmdname some_directory "
        print " "
        exit
fi

hme=` echo $HOME | cut -f1 -d' '  `
if [ "$hme" = "" ]; then
        print "\nError: \$HOME is not set!!\n"
        exit
fi

tmpfile=$hme/cvs_sinfo.tmp
rm -f $tmpfile

cur_dir=`pwd`
#echo $cur_dir

len=${#hme}
len=$(($len + 2))
#echo $len

subdir=` echo $cur_dir | cut -b $len-2000 `
#echo $subdir

if [ "$subdir" = "" ]; then
        fdname=$1
else
        fdname=$subdir"/"$1
fi

# Create subshell
if [ -f $1 ]; then
        (
        cd $hme
        clear
        cvs status $fdname
```

```
        )
elif [ -d $1 ]; then
        (
        cd $hme
        clear
        echo "  " >> $tmpfile
        echo "  ************************************" >> $tmpfile
        echo "        Overall Status of Directory" >> $tmpfile
        echo "  ************************************" >> $tmpfile
        cvs release $fdname 1>>$tmpfile 2>>$tmpfile << EOF
Y
EOF
        echo "\n   ------------------------------\n" >> $tmpfile

        aa=`cat $tmpfile | grep ^"M " | awk '{print $2}' `
        for ii in $aa
        do
                jj="(cd $hme; cvs status $subdir/$ii );"
                echo $jj | /bin/sh  \
                        | grep -v Sticky | awk '{if (NF != 0) print $0}' \
                        1>>$tmpfile 2>>$tmpfile
        done

        cat $tmpfile | grep -v ^? | grep -v "Are you sure you want to release" \
        | less
        rm -f $tmpfile
        )
else
        print "\nArgument $1 if not a file or directory"
        exit
fi
```

4.8 slog

NOTE : ***Korn shell /bin/ksh is got by installing pdksh*.rpm from Linux contrib cdrom***

Save this file as text file and chmod a+rx on it.

```
#!/bin/ksh

# CVS program slog
# Program to list history of the file in CVS

cmdname=`basename $0`

if [ $# -lt 1 ]; then
        print "\nUsage: $cmdname <filename> \n"
        exit
fi

# Check if file does not exist....
if [ ! -f $1 ]; then
        print "\nError: $1 is NOT a file. Aborting $cmdname ......"
        exit
fi
```

```
cvs log $1 | /usr/local/bin/less

print "\nDone $cmdname. $cmdname successful"
#print "\nTip (Usage): $cmdname <filename>\n"
```

4.9 sdif

NOTE : ***Korn shell /bin/ksh is got by installing pdksh*.rpm from Linux contrib cdrom***

Save this file as text file and chmod a+rx on it.

```
#!/bin/ksh

# CVS program sdif
# Program to see difference of the working file with CVS copy

cmdname=`basename $0`

Usage()
{
        print "\nUsage: $cmdname <filename> "
        print "$cmdname -r<rev1> -r<rev2> <filename> \n"
        exit
}
FLAG1=""
FLAG2=""
OARG1=""
OARG2=""
# Command getopt will not supported in next major release.
# Use getopts instead.
while getopts r:r: ii
do
        case $ii in
        r)
                if [ "$FLAG1" = "" ]; then
                        FLAG1=$ii;
                        OARG1="$OPTARG"
                else
                        FLAG2=$ii;
                        OARG2="$OPTARG"
                fi
                ;;
        ?) Usage; exit 2;;
        esac
done
shift ` expr $OPTIND - 1 `

if [ "$FLAG2" = "" ]; then
        FLAG2=r
        OARG2=HEAD
fi

if [ "$FLAG1" = "" ]; then
        cvs diff -r HEAD $1 | less
```

```
else
        cvs diff -$FLAG1 $OARG1 -$FLAG2 $OARG2 $1 | less
fi
```

4.10 sadd

NOTE : *Korn shell /bin/ksh is got by installing pdksh*.rpm from Linux contrib cdrom*

Save this file as text file and chmod a+rx on it.

```
#!/bin/ksh

# test
# CVS program sadd
# Program to add the file to CVS

cmdname=`basename $0`
if [ $# -lt 1 ]; then
        print "\nUsage: $cmdname <filename/directory> \n"
        exit
fi

# Check if file exists ....
if [ -f $1 ]; then
        cvs add $1
        exit
fi

if [ ! -d $1 ]; then
        print "\nArgument $1 is not a file and not a directory!"
        print "Usage: $cmdname <filename/directory> \n"
        exit
fi

# Argument is a directory name .....
hme=` echo $HOME | cut -f1 -d' '  `
if [ "$hme" = "" ]; then
        print "\nError: \$HOME is not set!!\n"
        exit
fi

cur_dir=`pwd`
len=${#hme}
len=$(($len + 2))
subdir=` echo $cur_dir | cut -b $len-2000 `

if [ "$subdir" = "" ]; then
        if [ -d $CVSROOT/$1 ]; then
                print "\nDirectory $1 already exists in CVSROOT"
                exit
        else
                # You are adding at root directory $CVSROOT
                if [ "$2" = "" -o "$3" = "" ]; then
                        print "\nUsage: $cmdname <directory> <vendor tag> <release tag>"
                        print "For example - "
```

```
                        print " $cmdname foo_directory V_1_0 R_1_0"
                        exit
                else
                        (
                        cd $1;
                        cvs import $1 $2 $3
                        )
                fi
        fi
else
        # If current directory exists in CVS...
        if [ -d $CVSROOT/$subdir ]; then
                if [ -d $CVSROOT/$subdir/$1 ]; then
                        print "\nDirectory $1 already in CVS repository!"
                else
                        cvs add $1
                fi
        else
                print "\nSub-directory $subdir does not exist in CVS"
                print "You need to first add $subdir to CVS"
                exit
        fi
fi
```

4.11 sdelete

NOTE : ***Korn shell /bin/ksh is got by installing pdksh*.rpm from Linux contrib cdrom***

Save this file as text file and chmod a+rx on it.

```
#!/bin/ksh

# CVS program sdelete
# Program to delete the file from CVS

cmdname=`basename $0`

if [ $# -lt 1 ]; then
        print "\nUsage: $cmdname <filename> \n"
        exit
fi

# Check if file does not exist....
if [ ! -f $1 ]; then
        # Try to get the file from CVS
        sget $1
        if [ ! -f $1 ]; then
                print "\nError: $1 does NOT exist in CVS repository. Aborting $cmdname ......"
                exit
        fi
fi

bkextn=cvs_sdelete_safety_backup
\mv -f $1 $1.$bkextn
```

```
cvs remove $1

print "\nsdelete command removes the file from CVS repository"
print "and archives the file in CVS Attic directory. In case"
print "you need this file in future than contact your CVS administrator"
print " "

print "\nDone $cmdname. $cmdname successful"
#print "\nTip (Usage): $cmdname <filename>\n"
\mv -f $1.$bkextn $1
```

4.12 sfreeze

NOTE : *Korn shell /bin/ksh is got by installing pdksh*.rpm from Linux contrib cdrom*

Save this file as text file and chmod a+rx on it.

```
#!/bin/ksh

# CVS program sfreeze
# Program to freeze and cut out the release of source tree from CVS

cmdname=`basename $0`

Usage()
{
        print "\nUsage: $cmdname symbolic_tag <directory name> "

        print "\nFor example :- "
        print "   cd \$HOME"
        print "   $cmdname  REVISION_1   mesa"
        print "To see the list of revisons do -"
        print "slog <filename> and see the symbolic name and do -"
        print "cvs history -T"

        print "\nTo create a branch off-shoot from main trunk, use"
        print "the -b and -r options which makes the tag a branch tag. This is"
        print "useful for creating a patch to previously released software"
        print "For example :- "
        print "   cd \$HOME"
        print "   cvs rtag -b -r REVISION_1   REVISION_1_1   mesa"
        print " "

#       print "\nTag info is located at \$CVSROOT/CVSROOT/taginfo,v"
#       print "You can do - cd $HOME; sget CVSROOT"
#       print "to see this file"
        exit
}

# Command getopt will not supported in next major release.
# Use getopts instead.
#while getopts r: ii
#do
#       case $ii in
#       r) FLAG1=$ii; OARG1="$OPTARG";;
```

```
#       ?) Usage; exit 2;;
#       esac
#done
#shift ‘ expr $OPTIND - 1 ‘

#echo FLAG1 = $FLAG1 , OARG1 = $OARG1

if [ $# -lt 2 ]; then
        Usage
fi

if [ ! -d $2 ]; then
        print "\nError: Second argument $2 is not a directory!"
        print "       Aborting $cmdname...."
        print " "
        exit
fi

# cvs rtag symbolic_tag <directory name>
cvs rtag $1 $2

print "\nDone $cmdname. $cmdname successful"
```

4.13 saddtree

NOTE : ***Korn shell /bin/ksh is got by installing pdksh*.rpm from Linux contrib cdrom***

Save this file as text file and chmod a+rx on it.

```
#!/bin/ksh

#####################################################################
# Sample Program to checkin a directory tree (let's say SAMP) into CVS
# Note that if SAMP directory is not in CVS than you would use sadd
# command and -
#       cd SAMP; cvs import SAMP V_1_0 R_1_0
# After running this program do -
#       cd $HOME/foo/SAMP
#       cvs import foo/SAMP V1_0 Rev_1_0
#####################################################################

hme=‘ echo $HOME | cut -f1 -d' '  ‘
if [ "$hme" = "" ]; then
        print "\nError: \$HOME is not set!!\n"
        exit
fi
sampdir=$hme/foo/SAMP

check_out_files()
{
        # Now check out the files
        tmp2f=$hme/tmp2.baksamp.sh

        cd $hme
        \rm -rf foo/SAMP
```

```
        cvs -w checkout foo/SAMP
        cd $hme/foo
        find SAMP -type f -print > $tmp2f

        cd $hme
        for ii in `cat $tmp2f`
        do
                iidir=`dirname $ii`
                iifile=`basename $ii`
                if [ "$iifile" = "Root" -o "$iifile" = "Repository" -o "$iifile" = "Entries" ]; then
                        continue
                fi
                jjdir=` echo $iidir | cut  -d'/' -f2-1000 `

                cp $hme/foo/SAMP.tobe/$jjdir/$iifile  $hme/foo/$iidir/$iifile
                echo "cp $hme/foo/SAMP.tobe/$jjdir/$iifile  $hme/foo/$iidir/$iifile "

                cvs add  foo/$iidir/$iifile
        done

        print
        print "============================================="
        print " Now run cvs commit foo/SAMP"
        print " After commit. Do - "
        print "         cd foo; rm -rf SAMP and "
        print " get fresh copy, sget SAMP"
        print " Verify with slog filename.samp to see new revision"
        print "============================================="
        print
}

check_out_files
```

5 CVS Documentation

At unix prompt type -

1. cvs –help
2. cvs –help-options
3. cvs –help-commands
4. cvs -H checkout
5. cvs -H commit
6. man cvs
7. man tkcvs
8. Visit <http://www.cyclic.com>
9. Visit <http://www.loria.fr/~molli/cvs-index.html>

The tkcvs <http://www.tkcvs.org> is the Tcl/Tk GUI interface to CVS. It also has online help.

- cd $HOME/src/foo.cpp
- tkcvs
- Click on foo.cpp
- Click on 'Revision Log Icon' which is located next to 'spectacle' icon
- This will display the branch TREE in the window. Now RIGHT Mouse button click on the text '1.3' and LEFT Mouse button click on text '1.1'. Than click on "Diff" button. This will display 2 pane-window!!
- Click on "Next" button to step thru more diffs. Click on "Center" to center the text.

There is also a Windows 95 client for CVS, and is called WinCVS <http://www.wincvs.org> WinCVS can be used along with Samba - <http://www.samba.org>

The essential command are -

- cvs checkout <filename >
- cvs update <filename>
- cvs add <file, ..>
- cvs remove <file, ..>
- cvs commit <file>
- cvs status <filename>
- cvs log <filename>
- cvs diff -r1.4 -r1.5 <filename> This gives diff between version 1.4 and 1.5 on filename.

6 Emacs Editor

Emacs is a powerful editor and it supports CVS/RCS - especially for revision merging and comparing. Emacs main site is at <http://www.emacs.org>.

7 Other Formats of this Document

This document is published in 10 different formats namely - DVI, Postscript, Latex, LyX, GNU-info, HTML, RTF(Rich Text Format), Plain-text, Unix man pages and SGML.

- You can get this HOWTO document as a single file tar ball in HTML, DVI, Postscript or SGML formats from - <ftp://sunsite.unc.edu/pub/Linux/docs/HOWTO/other-formats/> or <ftp://metalab.unc.edu/pub/Linux/docs/HOWTO/other-formats/>
- Plain text format is in: <ftp://sunsite.unc.edu/pub/Linux/docs/HOWTO> or <ftp://metalab.unc.edu/pub/Linux/docs/HOWTO>
- Translations to other languages like French, German, Spanish, Chinese, Japanese are in <ftp://sunsite.unc.edu/pub/Linux/docs/HOWTO> or <ftp://metalab.unc.edu/pub/Linux/docs/HOWTO> Any help from you to translate to other languages is welcome.

The document is written using a tool called "SGML tool" which can be got from - <http://www.xs4all.nl/~cg/sgmltools/> Compiling the source you will get the following commands like

- sgml2html cvs-rcs-howto.sgml (to generate html file)
- sgml2rtf cvs-rcs-howto.sgml (to generate RTF file)
- sgml2latex cvs-rcs-howto.sgml (to generate latex file)

This document is located at -

- <http://sunsite.unc.edu/LDP/HOWTO/CVS-RCS-HOWTO.html>

Also you can find this document at the following mirrors sites -

- <http://www.caldera.com/LDP/HOWTO/CVS-RCS-HOWTO.html>
- <http://www.WGS.com/LDP/HOWTO/CVS-RCS-HOWTO.html>
- <http://www.cc.gatech.edu/linux/LDP/HOWTO/CVS-RCS-HOWTO.html>
- <http://www.redhat.com/linux-info/ldp/HOWTO/CVS-RCS-HOWTO.html>
- Other mirror sites near you (network-address-wise) can be found at <http://sunsite.unc.edu/LDP/hmirrors.html> select a site and go to directory /LDP/HOWTO/CVS-RCS-HOWTO.html

In order to view the document in dvi format, use the xdvi program. The xdvi program is located in tetex-xdvi*.rpm package in Redhat Linux which can be located through ControlPanel | Applications | Publishing | TeX menu buttons.

```
To read dvi document give the command -
        xdvi -geometry 80x90 howto.dvi
And resize the window with mouse. See man page on xdvi.
To navigate use Arrow keys, Page Up, Page Down keys, also
you can use 'f', 'd', 'u', 'c', 'l', 'r', 'p', 'n' letter
keys to move up, down, center, next page, previous page etc.
To turn off expert menu press 'x'.
```

You can read postscript file using the program 'gv' (ghostview) or 'ghostscript'. The ghostscript program is in ghostscript*.rpm package and gv program is in gv*.rpm package in Redhat Linux which can be located through ControlPanel | Applications | Graphics menu buttons. The gv program is much more user friendly than ghostscript. Ghostscript and gv are also available on other platforms like OS/2, Windows 95 and NT.

```
To read postscript document give the command -
        gv howto.ps

To use ghostscript give -
        ghostscript howto.ps
```

You can read HTML format document using Netscape Navigator, Microsoft Internet explorer, Redhat Baron Web browser or any other web browsers.

You can read the latex, LyX output using LyX a "X-Windows" front end to latex.